


BANBA

Rev03_April 2024



GENERAL INFORMATION

Rig Type	Jack Up, Marathon LeTourneau 82 SD-C
Rig Design	Conventional, Self-elevating independent legs, cantilever drill floor
Accommodation Capacity	118
Helideck	Sikorski S-61N, 9.3 ton max load
Hull Dimensions (length, width, depth)	207.33 ft x 176 ft x 20 ft
Min/Max Water Depth	13 to 250 ft
Max Drilling Depth	16,150 ft
Cantilever Max Load	1,000,000 lbs
Rotary Reach	47 ft longitudinal; 10 ft transverse either side of Centerline
Legs length / leg length below hull	360.33 ft (including spudcans) / 304 ft
Spudcan Diameter / bearing area	40 ft / 1,256.64 ft ²
VDL (Operating) / VDL (Transit)	5,000 kips / 3,934.39 kips
Jacking System	LeTourneau AC electric rack and pinion system, 20 each leg, 1.5ft/min speed

DRILLING EQUIPEMENT

Derrick	Make - L x W x H	Continental Ensco – 160 ft x 30 ft x 30 ft
	Max. Hook Load	800,000 lbs with 14 lines strung
	Racking capacity	16,000 ft – 169 stands 5" DP
	Setback load	450 kips
Top Drive	Make Model	VARCO TDS 4H
	Output Power	1,130 hp
	Rated Capacity	1,300 kips, 59,000 ft-lbs Low Gear / 32,500 ft-lbs High gear
Drawworks	Make Model	NATIONAL 1320-UE
	HP Rating	2,000 hp
	Brakes	Elmagco 7838 with battery Back up
Torque Wrench	NOV ST-100 Iron Roughneck	
Rotary Table	National C-375, 37-1/2" with 800 hp electric drive, 650 ton rated capacity	
Travelling Block	National 760-H-650, 650 ton rated capacity, 60" sheaves with 1-1/2" line groove	

WELL CONTROL SYSTEM

Diverter	30" MSP 1000 psi
Annular	Shaffer Spherical BOP 13-5/8" x 5,000 psi
BOP	2 x T3 Type U 13-5/8" x 10,000 psi
BOP Outlets	2 x 4-1/16" side outlets each DBL
BOP Control System	T3 /1B603608B15T33A-P-API, 682 US gal reservoir, 3000 psi Regulated to 1500 psi system working pressure, 360 US gal Accumulator Capacity without precharge
Choke Manifold	T3 10,000 psi H2S service

MUD SYSTEM

Mud Pumps	Number x Make Model HP Rating Max Pressure	3 x NATIONAL 12-P-160 Triplex 1,600 hp each pump 5,000 psi
Shale Shakers	4 x VSM 300, double deck with scalping	
System max pressure	7,500 psi	
Degasser	Brandt DG 12, 28.5 gpm	

CRANES

Crane 1 (Port - Aft)	LeTourneau PCM120AS, 100 ft boom, 45.3T SWL at 78°
Crane 2 (Port - Fwd)	LeTourneau PCM120AS, 120 ft boom, 38.7T SWL at 79°
Crane 3 (Stbd)	LeTourneau PCM120AS, 100 ft boom, 45.3T SWL at 78°

POWER GENERATION

Main Engines	3 x EMD 645E9B diesel engines, 6,915 hp total
Generators	3 x NOV Baylor Mod AB-21-6-5023 generators
Emergency	1 x GMDD 550 hp

STORAGE CAPACITY

Fuel	1,480 bbl	Potable Water	1,729 bbl
Drill Water	5,421 bbl	Bulk Mud	3,440 ft ³
Liquid Mud	1,617 bbl	Bulk Cement	3,877 ft ³
Brine	0 bbl	Bulk Barite	3,877 ft ³
Base Oil	2,896 bbl	Sack Room	5,000 sacks

TUBULARS

Drill pipes	<ul style="list-style-type: none"> 15,780 ft / 501 jt x 5" DP NC50 Range 2 1,570 ft / 50 jt x 4" DP XT 39 Range 2
HWDP	<ul style="list-style-type: none"> 43 jt x 5" HWDP NC50 Range 2 25 jt x 3-1/2" HWDP NC38 Range 2 35 jt x 4" HWDP XT39 Range 2
Drill Collars	<ul style="list-style-type: none"> 10 jt x 9-1/2" DC 7-5/8" REG Range 2 36 jt x 6-3/4" DC 6-5/8" REG Range 2 36 jt x 8-1/4" DC 6-5/8" REG Range 2 9 jt x 4-3/4" DC NC38 Range 2