



Diving Support Barge

BRAN 3



Diving Support Barge

The Bran 3 diving support barge is a reliable and versatile solution for underwater operations. With its specialized equipment and capabilities, the barge provides essential support for diving missions, ensuring safety and efficiency in subsea exploration and maintenance tasks.

Main data

GENERAL

IMO:	N/A
Callsign:	J8B5782
Gross Tonnage:	647 [T]
Net Tonnage:	194 [T]
Deadweight:	N/A
Year of Build:	2010
Place of Build:	Szczecin, Poland
Flag:	St. Vincent and the Grenadines
Port of registry:	Louis, Mauritius
Owner:	DERMOR Inc.
Service area:	West coast of Africa. Unrestricted Navigation.

DIMENSIONS

Length O.A.:	46.08 [m]
Beam:	13.20 [m]
Draft:	3.60 [m]
Deck Load:	2.50 [T/m ²]

CLASSIFICATION

- INSB

ACCOMMODATION

Heated and Airconditioned up to 18 Persons

CONTACT INFORMATION

Tel:	+242 05 315 71 07
Iridium:	N/A
Email:	bm.bran3@dixstone.com

COMMUNICATIONS

- VSat
- Portable VHF Radios

MACHINERY

- 2x Generator Volvo D7A-A
- 1x Generator Volvo D5A-A
- Keel Cooled
- Watermaker
- Sewage plant

CAPACITIES

Fuel Capacity:	37 [m ³] + 3.5 m ³ daily tank
Fresh Water:	22 [m ³]
Technical Water:	130 [m ³]
Sewage:	7.5 [m ³]

MOORING

6 Mooring winches
600 Mtr mooring lines

Deck Cranes

FASSI F600A.24

2400 [Kg] @ 18.60 [m]

2900 [Kg] @ 16.15 [m]

3650 [Kg] @ 13.80 [m]

4500 [Kg] @ 11.50 [m]

5490 [Kg] @ 9.50 [m]

6920 [Kg] @ 7.60 [m]

9915 [Kg] @ 5.80 [m]

12745[Kg] @ 4.15 [m]

16000[Kg] @ 3.20 [m]

HEILA HLRM CRANE 140--4SLK

5100 [kg] @ 18.00 [m]

6200 [kg] @ 15.30 [m]

8150 [kg] @ 12.75 [m]

10450[kg] @ 10.19 [m]

14600[kg] @ 7.64 [m]

5000 [Kg] Hoist capacity

Deck Winches

DEGRA MOORING WINCHES

35 [t] Mooring winches

Max pull 350 Kn @ 300 Bar

Nomeline pull 300 Kn @ 260 Bar

Max speed 30m / Min

WORK WINCHES

15 [t] Winches



BRAN 3
Technical drawing & data

