



Multicat

SILIMELEN



Multicat

The Sili Melen vessel is a highly capable and versatile workhorse. Designed to perform various functions, including towing, mooring, pushing, anchor handling, dive support, dredge support, supply, and survey operations. With its robust construction and adaptable capabilities, this vessel is an ideal choice for a wide range of marine tasks.

Main data

GENERAL

IMO:	9586409
Callsign:	J8B6074
Mmsi:	375772000
Gross Tonnage:	254 [T]
Net Tonnage:	76 [T]
Deadweight:	N/A
Year of Build:	2010
Place of Build:	N/A
Flag:	St. Vincent and the Grenadines
Port of registry:	Kingstown
Owner:	N/A

DIMENSIONS

Length O.A.:	25.90 [m]
Beam:	11.00 [m]
Draft:	2.63 [m]
Deck Load:	6.00 [t/m ²]
Bollard pull:	30 [T]

CLASSIFICATION

- Bureau Veritas 1 + Hull
- Machinery Special Service

CONTACT INFORMATION

Tel.:	+31 652360933
Iridium:	+881677715626
Email:	silimelen@dixstone.com

COMMUNICATIONS

- Iridium
- 2 DSC VHF Radios
- INMARSAT C terminal
- GSM Phone
- E-Mail

CAPACITIES

Fuel Capacity :	106 [m ³]
Fresh Water:	49 [m ³]
Deck Area:	± 140 [m ²]

ACCOMMODATION

Heated and Airconditioned up to 7 Persons

Main data

PROPULSION

- 2 Caterpillar C32 ACERT
- Total Horse Power 2,700 [HP]
- Twin Disc Reduction Gearboxes
- Fixed Props in Forward Nozzles
- Box Cooled
- Speed 10 Knots
- Generators 2 x Caterpillar 200 [kW]
- 360° bowthruster 280 [kW]

NAV EQUIPMENT

- Magnetic Compass
- Satellite compass
- Daylight Viewing Radars
- Speed Log
- Echo Sounder
- Electronic Chart
- Plotter
- Watch Keeping Alarm
- AIS
- GPS Navigator
- NAVTEX
- Talk Back Unit
- Autopilot

DECK EQUIPMENT

HEILA HLRM CRANE 230 – 4SL

- 10300 [kg] @ 16.30 [m]
- 12200 [kg] @ 14.40 [m]
- 15400 [kg] @ 12.23 [m]
- 18900 [kg] @ 10.06 [m]
- 24400 [kg] @ 7.89 [m]

HYDRAVISION WINCHES

- 80 [T] Anchor handling Winch
- 50 [T] Towing Winch
- 15 [T] Tugger Winch

TOWING PINS

SWL 30 [T], Based on max wire. angle of 45° to the centerline of the vessel

WIRE/CHAIN STOPPER

- SWL 50 [T]
- Max wire/chain insert 65 [mm]

OTHER EQUIPMENT

- Towing Hook
- Push Bow
- Wheelhouse Winch Controls
- Fuel Supply Pump
- Freshwater Supply Pump


OPTIONAL A-FRAME

- Frame SWL 50 [T]
- Outreach 2.7 [m] from stern
- 2x 20 [t] Winches



SILIMELEN

Technical drawing & data



SILIMMELLEN

Technical drawing & data