



Anchor Handling Tug Supply Vessel

SKOUL GLAZ

The information contained in this specification sheet is for information purposes only. © 2023 DIXSTONE. All rights reserved.



Anchor Handling Tug Supply Vessel

The Skoul Glaz vessel is a versatile and dynamic vessel capable of towing, mooring, anchor handling, offshore supply, and serving as a firefighting vessel. With its multifunctional capabilities, this vessel ensures efficient and reliable support in various offshore operations, including firefighting in emergency situations.

Main data

GENERAL

IMO:	9573579
Callsign:	J8B6142
Mmsi:	377578000
Gross Tonnage:	1733 [T]
Net Tonnage:	519 [T]
Deadweight:	1435 [T]
Year of Build:	2010
Place of Build:	N/A
Flag:	St. Vincent and the Grenadines
Port of registry:	Kingstown
Owner:	DERMOR Inc.

DIMENSIONS

Length O.A.:	59.78 [m]
Beam:	15.00 [m]
Draught:	4.30 [m]
Deck Load:	542 [mT]
Displacement:	2676 [T]
Bollard pull:	80 [mT]

CLASSIFICATION

- INSB

CONTACT INFORMATION

VSAT:	+4723675920
Iridium:	+881677115205
Email:	skouलगlaz@dixstone.com

COMMUNICATIONS

- VSat
- Email/ IP Voice Facilities
- GMDSS radio system/ A3
- Inmarsat Fleet 77
- Iridium

CAPACITIES

Fuel Capacity:	606 [m³]
Fresh Water:	359 [m³]
Liquid Mud:	652 [m³]
FOAM:	14 [m³]
Bulk Mud:	148 [m³]
Ballast Water:	448 [m³]
Deck Area:	± 302 [m²]

ACCOMMODATION

- 10 x Crew
- 12 x Guest

Main data

SAFETY

- FIFI 1 System: 2 x Monitors 1200 [m³/h]
- 2 x Pumps 1500 [m³/h]
- Water Spray Protection
- MOB boat/ Davit
- Life Saving Arrangement
- Stand-by Rescue Equipment

NAV EQUIPMENT

- Radars
- Depth Sounder
 - Nav computer
 - Watch Keeping Alarm
 - AIS
 - Navtex
 - Sart
 - SSAS

DYNAMIC POSITIONING (DP) CLASS 2

- DGPS
- Cyscan
- Laser Reference Unit
- Independent joystick system
- Sensors/Monitoring as per Class 2

MACHINERY/ PERFORMANCE

- Main engine: 3 x Cummins QSK-60-D(M)
- Output Power: 3 x 1824 [kW]
- Emerg. Gen: 1 x Cummins 6CTA8.3-D, 181 [kW]
- Bow thruster: 2 x Berg BFTT 316, 560 [kW]
- Propulsion: 2 x Azimuth Z-Drive Steerprop
- Propulsion: 1 x Fixed Z-Drive @ CL Steerprop
- Max speed: 13.5 [Kn] 22[m³] day
- Service speed: 12 [Kn] 16[m³] day
- Eco speed: 10 [Kn] 8.3[m³] day
- Standby mode: 5.4[m³] day

ADDITIONAL INFORMATION

- Crane: 1 x 2 [T] @ 6.5 [m] outreach
- Towing/ AH winch: Drum Waterfall 150 [T] pull, 250 [T] break
- Towing/ AH winch Cap: 1500 [m] x 2 [Inch]
- Gob eye and Seat fitted
- Tugger winch: 2 x 10 [T] pull 15 [T] Brake
- Tugger winch Cap: 2 x 250 [m]
- Storage reel Cap: 1500 [m] Dia 57 [mm]
- Cable filters: 2 for 2" 1/2 and 3" chains
- Towing pins/ Shark jaw: 200 [T] Manu: Plimsoll
- Stern roller: 1,500 [mm] dia. x 2,500 [mm] length



SKOULGLAZ

Technical drawing & data



SKOUL GLAZ

Technical drawing & data

